

TUBOMATIC H144 ES

CODE: TUBH144ES
CRIMPING (STANDARD VOLUME CRIMPING)

TUBOMATIC H144 EL

CODE: TUBH144EL
CRIMPING (STANDARD VOLUME CRIMPING)



MAIN FEATURES



IDEAL FOR ANY TYPE OF FITTING



MACH TOUCH-SCREEN ELECTRONIC CONTROL
H144 ES



INDUSTRIAL HOSE CRIMP CALCULATOR
H144 ES



WARNING LED
H144 EL



VERNIER DIAL
H144 EL



ELECTRO-MECHANICAL CONTROL
H144 EL



IDEAL FOR YOUR WORKSHOP



PROTRACTOR FOR FITTINGS ORIENTATION

TECHNICAL DATA

	H144 ES	H144 EL
CRIMPING FORCE	440 US TONS	440 US TONS
6 SPIRALS 2 PIECES	2" 1/2	2" 1/2
INDUSTRIAL HOSE	4"	4"
MAX Ø	144 mm (5.6")	144 mm (5.6")
CRIMPING / HOUR	703 ^Δ	703 ^Δ
DIE OPENING	Ø + 1.7"	Ø + 1.7"
90° FITTINGS	2"	2"
STANDARD VOLTAGE	ANY 60HZ 3PH	ANY 60HZ 3PH
MOTOR POWER	5.5 KW (7.5 HP) - A= 10,74	5.5 KW (7.5 HP) - A= 10,74
DIMENSIONS LXWXH	33"X30.3"X33.6"	33"X25.9"X33.6"
WEIGHT WITHOUT OIL	1213 Lbs	1210 Lbs
OIL (NOT INCLUDED)	110 LT. (29 US gal)	110 LT. (29 US gal)
SETTABLE RE-OPENING TIME AFTER CRIMPING	-	■
SETTABLE CRIMPING TIME	-	■
USB KIT	■	-

ACCESSORIES

	H144 ES	H144 EL
PRESSURE CONTROL SYSTEM KIT	■	-
QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL	■	-
MULTISTEP CRIMPING DIAMETERS	■	-
DISPENSER + PATENTED QUICK CHANGE TOOL	■	■
BASE	■	■
BACK MIRROR	■	■
CLEANING AND MAINTENANCE KIT	■	■
ELECTRIC PEDAL	INCLUDED	■

DIAMETER (mm)	10	12	14	16	19	22	25	29	34	38	42	46	50	54	58	63	69	73	77	86	90	96	103	106	111	116	121	126	131
DIES LENGTH (mm)	60	60	60	60	60	60	60	70	70	85	85	95	95	95	95	100	100	100	120	120	150	120	130	130	130	130	130	130	130
H144 ES																													
H144 EL																													

Δ THEORETICAL WITH 1/2" Δ Ø 6 mm HOSE
ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED

Product specifications could be modified without prior notice.