

TF3/E
CODE: TAGLTF3D/E
CUTTING

TF2/E
CODE: TAGLTF2D/E
CUTTING

TF1/E
CODE: TAGLTF1D/E
CUTTING



MAIN FEATURES



SAFETY PROTECTIONS



SUCTION CONNECTION



TOOTHED BLADE



MANUALLY OPERATED



IDEAL FOR ON-SITE SERVICE



RECESSED BLADE FOR A GREATER SAFETY



ALSO AVAILABLE IN 12V - 24V

TECHNICAL DATA

	TF3/E	TF2/E	TF1/E
6 SPIRALS	2"	1" 1/2	1"
4 SPIRALS	-	2"	1" 1/4
2 BRAIDS	-	2"	1" 1/4
MAX Ø	3.3"	2.9"	2.3"
REVOLUTIONS/MINUTE	2900	2900	2900
BLADE Ø	350 mm (13.7")	250 mm (9.8")	250 mm (9.8")
STANDARD VOLTAGE	ANY 60HZ 3PH/1PH	ANY 60HZ 3PH/1PH	ANY 60HZ 3PH/1PH
DIMENSIONS LXWXH	29.9"x20.9"x20"	25.5"x27.5"x16.5"	20.6"x25.9"x17.5"
WEIGHT	131 Lbs	97 Lbs	66 Lbs
MOTOR POWER	3 KW (4 HP)	3 KW (4 HP)	1.1 KW (1.5 HP)

ACCESSORIES

	TF3/E	TF2/E	TF1/E
CENTERING DEVICE + METER COUNTER (MAX 2")		■	-

COMPACT AND INEXPENSIVE EQUIPMENT, IDEAL FOR ON-SITE SERVICE