

TF3
CODE: TAGLTF3D
CUTTING

TF3 PI
CODE: TAGLTF3DPI
CUTTING

TF2
CODE: TAGLTF2D
CUTTING



MAIN FEATURES



SAFETY PROTECTIONS



SUCTION CONNECTION



TOOTHED BLADE



IDEAL FOR YOUR WORKSHOP



RECESSED BLADE
FOR A GREATER SAFETY



PNEUMATIC INPUT

TF3 PI

TECHNICAL DATA

	TF3	TF3 PI	TF2
6 SPIRALS	2"	2"	1" 1/2
4 SPIRALS	2" 1/2	2" 1/2	2"
2 BRAIDS	3"	3"	2"
MAX Ø	3.9"	3.9"	2.9"
REVOLUTIONS/MINUTE	2900	2900	2900
BLADE Ø	400 mm (15.7")	400 mm (15.7")	250 mm (9.8")
STANDARD VOLTAGE	ANY 60HZ 3PH	ANY 60HZ 3PH	ANY 60HZ 3PH/1PH
DIMENSIONS LXWXH	39.3"x27.9"x45.2"	40.3"x27.5"x45.2"	33"x21.6"x45.2"
WEIGHT	419 Lbs	530 Lbs	290 Lbs
MOTOR POWER	5.5 KW (7.5 HP) - A= 1014	5.5 KW (7.5 HP) - A= 1014	3 KW (4 HP)
PNEUMATIC INPUT	-	MAX 7 BAR (100 PSI)	-

ACCESSORIES

	TF3	TF3 PI	TF2
STROKE COUNTER	■	■	■
MEASURING HOSE HOLDER	■	■	■
CENTERING DEVICE + METER COUNTER (MAX 2")	■	■	■
MECHANICAL PEDAL CONTROL (INCLUDED)	■	-	■
PEDAL-EQUIPPED PNEUMATIC CONTROL (INCLUDED)	-	■	-
CUTTING SPEED ADJUSTMENT DEVICE (INCLUDED)	-	■	-

