

SPF2

CODE: SPELSPF2
SKIVING

SPF2/E

CODE: SPELSPF2/E
SKIVING

SPF1

CODE: SPELSPF1
SKIVING



MAIN FEATURES



INTERNAL SKIVING



EXTERNAL SKIVING



PNEUMATIC VICE

SPF2



SAFETY PROTECTIONS

SPF2/E
SPF2



DRAWER FOR SHAVINGS

SPF2/E
SPF2



ALSO AVAILABLE IN 12V

SPF2/E



IDEAL FOR ON-SITE SERVICE

SPF2/E
SPF1

TECHNICAL DATA

	SPF2	SPF2/E	SPF1
EXTERNAL SKIVING	2"	2"	2"
INTERNAL SKIVING	2"	2"	2"
REVOLUTIONS/MINUTE	300	300	-
PNEUMATIC INPUT	MAX 7 BAR (100 PSI) OPTIONAL	-	-
WEIGHT	181 Lbs	110 Lbs	15 Lbs
DIMENSIONS LXWXH	25.5"x17.2"x42.7"	26.5"x21"x17.2"	18.8"x9.4"x3.9"
STANDARD VOLTAGE	ANY 60HZ 3PH/1PH	ANY 60HZ 3PH/1PH	-
MOTOR POWER	0.75 KW (1 HP)	0.75 KW (1 HP)	-

ACCESSORIES

	SPF2	SPF2/E	SPF1
ELECTRIC PEDAL (INCLUDED)		■	■
TOOL HOLDER		■	■

SPF2



SINGLE MANDREL
WITH DOUBLE KNIFE,
ONE FOR EACH DIAMETER

SPF2



OPTIONAL
PNEUMO-HYDRAULIC VICE

SPF2/E



FIXED SKIVING MANDREL WITH ONE CUTTER ONLY,
PROVIDED WITH A MILLIMETRIC RULER TO SET THE
SKIVING DISTANCE

SPF1



SPF2/E



DRAWER FOR SHAVINGS