

TUBOMATIC H135 24V/12V

CODE: TUBH13524V - TUBH13512V
CRIMPING (STANDARD VOLUME CRIMPING)

TUBOMATIC H130 24V/12V

CODE: TUBH13024V / TUBH13012V
CRIMPING (STANDARD VOLUME CRIMPING)

TUBOMATIC H83/E 12V

CODE: TUBH83/E12V
CRIMPING (STANDARD VOLUME CRIMPING)



MAIN FEATURES



IDEAL FOR ANY TYPE OF FITTING



24V - 12V



LED INDICATING WHEN THE SET CRIMPING DIAMETER IS REACHED



VERNIER DIAL



ELECTRO-MECHANICAL CONTROL

H135



IDEAL FOR ON-SITE SERVICE

TECHNICAL DATA

	H135 24V/12V	H130 24V/12V	H83/E 12V
CRIMPING FORCE	CRIMPING FORCE H135 - 330 US TONS	CRIMPING FORCE H130 - 275 US TONS	150 US TONS
6 SPIRALS 2 PIECES	2"	1" 1/4	1"
4 SP 2 PIECES	-	2"	1" 1/2 [○]
4 SH 2 PIECES	-	-	1" 1/4
INDUSTRIAL HOSE	3"	3"	-
MAX Ø	111 mm (4.3") *	111 mm (4.3") *	64 mm (2.5") [◇]
DIE OPENING	Ø + 1.6"	Ø + 1.3"	Ø + 1.6"
90° FITTINGS	2"	2"	1" 1/4 [○]
STANDARD VOLTAGE	24V / 12V D.C.	12V / 24V D.C.	12V D.C.
MOTOR POWER	2,5 KW (3.4 HP) (12V) 4 KW (5.3 HP) (24V)	1.6 KW (2.1 HP)	2.1 KW (2.82 HP)
DIMENSIONS LXWXH	26.4"x16.6"x30"	20.6"x17.2"x27.8" (12V) 26.5"x17.2"x27.8" (24V)	19.9"x16.5"x16.3"
WEIGHT WITHOUT OIL	639 Lbs	434 Lbs (12V) 485 Lbs (24V)	200,6 LBS
OIL (NOT INCLUDED)	10 LT. (2.5 US gal)	10 LT. (2.5 US gal)	6 LT (1.58 US gal)
CYLINDER	-	-	SINGLE EFFECT

ACCESSORIES

	H135 24V	H130 12V	H83/E 12V
DISPENSER + PATENTED QUICK CHANGE TOOL			
PORTABLE DISPENSER + STANDARD QUICK CHANGE TOOL			
BASE			
CLEANING AND MAINTENANCE KIT		-	-

ALSO AVAILABLE WITH SEPARATE POWER PACK



DIAMETER (mm)	10	12	14	16	19	22	25	29	34	38	42	46	50	54	58	63	69	73
DIES LENGTH (mm)																		
H135 24V - H130 12V	60	60	60	60	60	60	60	70	70	85	85	85	95	95	95	100	100	100
H83/E 12V	60	60	60	60	60	60	60	70	70	85	85	85	-	-	-	-	-	-

◇ WITH SPECIAL DIES Ø 54 mm UPON REQUEST

○ WITH SPECIAL DIES

*WITH SPECIAL DIES Ø 104 mm UPON REQUEST

ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED