

UNISPEED USFL 24/37 ES

CODE: UNISUSFL2437ES

FLARING & PREASSEMBLY

UNISPEED USFL 24/37 ES 6/18

CODE: UNISFL2437ES618

FLARING & PREASSEMBLY



PATENT PENDING CYLINDER

MAIN FEATURES



DIN2353 RINGS
PREASSEMBLY



37° FLARING



TOUCH-SCREEN
ELECTRONIC CONTROL



IDEAL FOR VOLUME
PRODUCTION



EQUIPPED WITH WHEELS



FRONT TOOL-HOLDER
COMPARTMENT



IDEAL FOR THE
AUTOMOTIVE INDUSTRY

USFL24/37 ES 6/18

TECHNICAL DATA

	USFL 24/37 ES	USFL 24/37 ES 6/18
24° PREASSEMBLY	6→42X4 mm	6→18X2 mm
37° FLARING	1/4"→ 1" 1/2 X 0.15"	1/4" → 5/8" X 0.08"
MATERIALS	AISI 316 TI - ST 37.4	AISI 316 TI - ST 37.4
WEIGHT WITHOUT OIL	330 Lbs	291 Lbs
DIMENSIONS LXWXH	23"X23.6"X45.2"	31.8"X31.4"X42.3"
STANDARD VOLTAGE	ANY 60HZ 3PH	ANY 60HZ 3PH
MOTOR POWER	1.5 KW (2 HP)	0.75 KW (1 HP)
OIL (NOT INCLUDED)	15 LT. (4 US gal)	13 LT. (3.5 US gal)

USFL 24/37 ES

Equipped with a double working level: upper level for bends up to 180°, lower level for standard tubes

OPTIONAL

	24/37 ES	24/37 ES 6/18
ELECTRIC PEDAL		
37° FLARING BLOCK (6→42)		-
37° FLARING BLOCK (6→18)		
TOOL HOLDER (6→42)		-
TOOL HOLDER (6→18)		

USFL 24/37 ES 6/18

Suitable for tubes with extreme bends up to 180° (shaped rigid tubes, steel and hose combined connections)



37° FLARING TOOLS:
supplied according to UNI ISO 8434-2 and DIN 3949 regulations

EQUIPMENT SUITABLE TO PROCESS RIGID TUBES
IN STAINLESS (AISI 316 TI) AND CARBON (ST 37.4) STEEL