

UNISPEED USFL/01 ES

CODE: UNISUSFLES
FLARING & PREASSEMBLY

UNISPEED USFL/01

CODE: UNISUSFL
FLARING & PREASSEMBLY



MAIN FEATURES



DIN2353 RINGS
PREASSEMBLY



37° FLARING WITH THE
ADDITION OF A DEDICATED
STEEL FLARING BLOCK



ALSO AVAILABLE IN 12V



MANUAL PRESSURE
ADJUSTMENT



IDEAL FOR ON-SITE
SERVICE



AUTOMATIC TOOLS
IDENTIFICATION
SYSTEM
USFL/01 ES

TECHNICAL DATA

	USFL/01 ES	USFL/01
24° PREASSEMBLY	6→42X4 mm	6→42X4 mm
37° FLARING	1/4 → 1" 1/2 X 0.15"	1/4 -> 1" 1/2 X 0.15"
MATERIALS	AISI 316 TI - ST 37.4	AISI 316 TI - ST 37.4
WEIGHT	165 KG	132 Lbs
DIMENSIONS LXWXH	27.2"X22.8"X43.7"	17.7"X24.8"X10.6"
STANDARD VOLTAGE	ANY 60HZ 3PH	ANY 60HZ 3PH/1PH
MOTOR POWER	1.8 KW (2.5 HP)	0.75 KW (1 HP)
OIL (NOT INCLUDED)	20 LT. (5 US gal)	-

USFL/01 ES

Automatic tool identification system and automated pressure setting, possibility to manually store recipes and recall them automatically, thanks to automatic tools identification

OPTIONAL

	USFL/01 ES	USFL/01
PEDAL		-
37° FLARING BLOCK (6→42)		
TOOL HOLDER (6→42)		

EQUIPMENT SUITABLE TO PROCESS RIGID TUBES
IN STAINLESS (AISI 316 TI) AND CARBON (ST 37.4) STEEL

37° FLARING TOOLS:
supplied according to UNI ISO 8434-2 and DIN 3949 regulations