

TUBOMATIC H130 ES

CODE: TUBH130ES

CRIMPING (STANDARD VOLUME CRIMPING)

TUBOMATIC H130 EL

CODE: TUBH130EL

CRIMPING (STANDARD VOLUME CRIMPING)

TUBOMATIC H130/E EL

CODE: TUBH130/EEL

CRIMPING (STANDARD VOLUME CRIMPING)



ALSO AVAILABLE WITH
PORTABLE DIES HOLDER



MAIN FEATURES



IDEAL FOR ANY TYPE OF FITTING



MACH TOUCH-SCREEN
ELECTRONIC CONTROL

H130 ES



ELECTRO-MECHANICAL
CONTROL

**H130 ES
H130 EL**



WARNING LED

H135 EL



VERNIER DIAL

**H130 EL
H130/E EL**



IDEAL FOR YOUR WORKSHOP



PROTRACTOR FOR FITTINGS
ORIENTATION

**H130 ES
H130 EL**

TECHNICAL DATA

	H130 ES	H130 EL	H130/E EL
CRIMPING FORCE	210 US TONS	210 US TONS	275 US TONS
6 SPIRALS 2 PIECES	1" 1/4	1" 1/4	1" 1/4
4 SP 2 PIECES	2"	2"	2"
INDUSTRIAL HOSE	3"	3"	3"
MAX Ø	130 mm (5.1") [◇]	124 mm (4.9") [◇]	111 mm (4.3") [◇]
CRIMPING / HOUR	780 [□]	780 [□]	246 [□]
DIE OPENING	Ø + 1.3"	Ø + 1.3"	Ø + 1.3"
90° FITTINGS	2"	2"	2"
STANDARD VOLTAGE	ANY 60HZ 3PH/1PH	ANY 60HZ 3PH/1PH	ANY 60HZ 3PH/1PH
MOTOR POWER	4 KW (5.5 HP)	4 KW (5.5 HP)	2.2 KW (2.9 HP)
DIMENSIONS LXWXH	29.9"x27.1"x28.7"	29.9"x26.5"x28.1"	26.2"x23.1"x26"
WEIGHT WITHOUT OIL	650 Lbs	650 Lbs	454 Lbs
OIL (NOT INCLUDED)	65 LT. (17 US gal)	65 LT. (17 US gal)	22 LT. (6 US gal)
SETTABLE RE-OPENING TIME AFTER CRIMPING	-	■	-
SETTABLE CRIMPING TIME	-	■	-
USB KIT	■	-	-

ACCESSORIES

	H130 ES	H130 EL	H130/E EL
PRESSURE CONTROL SYSTEM	■	-	-
QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL (INCLUDED)	■	-	-
MULTISTEP CRIMPING DIAMETERS	■	-	-
PATENTED QUICK CHANGE TOOL	■	■	■
BASE	■	■	■
BACK MIRROR	■	■	-
CLEANING AND MAINTENANCE KIT	■	■	■
ELECTRIC PEDAL	INCLUDED	■	■

DIAMETER (mm)	10	12	14	16	19	22	25	29	34	38	42	46	50	54	58	63	69	73
DIES LENGTH (mm)	60	60	60	60	60	60	60	70	70	85	85	95	95	95	95	100	100	100
H130 ES - H130 EL H130/E EL																		

◇ THEORETICAL WITH 1/2" Δ Ø 6 mm HOSE

■ TEORICO CON TUBO 1/2" Δ Ø 6 mm

ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED