

BC 1200-2000 ES AND BC 1200-2000 ES WATER

CODE: BC1200-BC2000-BC1200/WATER-BC2000/WATER

TESTING



WATER VERSION WITH CHAMBER AND COMPONENTS IN STAINLESS STEEL

PNEUMO-HYDRAULIC PUMP

MAIN FEATURES



WATER TESTS
BC 1200 ES WATER
BC 2000 ES WATER



TOUCH-SCREEN
ELECTRONIC CONTROL



INTERNAL LIGHTING



SHOCK-PROOF
TESTING WINDOWS



SLIDING MANIFOLD



TEMPERATURE
WARNING SIGNAL



AUTOMATIC
DOOR OPENING



USB CONNECTION
CONFIGURATION



PDF FILES PRINTING

TECHNICAL DATA

STATIC PRESSURE	1200-2000 BAR (17400-29000 PSI)	
DYNAMIC PRESSURE	1200-2000 BAR (17400-29000 PSI)	
1200 BAR MIN. STARTING PRESSURE	30 BAR (435 PSI)	
2000 BAR MIN. STARTING PRESSURE	50 BAR (725 PSI)	
PRESSURE CONTROL	AUTOMATIC	
TEST	AUTOMATIC	
TYPE OF DRIVE	PNEUMATIC INTENSIFIER	
TESTING LIQUID	FLUID OR WATER	
N° MANIFOLDS	2	
N° CONNECTIONS PER MANIFOLD	15X1/4" BSP	
LIQUID FILLING	AUTOMATIC	
FILLING FLOW	FLUID VERSION 25 LT./MIN. (6.5 US gal/MIN.)	WATER VERSION 17 LT./MIN. (4.5 US gal/MIN.)
PRESSURE PUMP FLOW	BC 1200 1.55 LT./MIN. (0.4 US gal/MIN.)	BC 2000 0.525 LT./MIN. (0.14 US gal/MIN.)
HOSE EMPTYING SYSTEM	AUTOMATIC	
PRESSURE DISCHARGE	AUTOMATIC	
PRESSURE DISPLAY	DIGITAL	
AUTOMATIC DOOR SAFETY DEVICE	FLUID VERSION ELECTRIC	WATER VERSION MECHANICAL
STANDARD CHAMBER DIMENSIONS	86.6"X35.4"	
BENCH DIMENSIONS	106.2"X38.5"X66.9"	
AIR CONSUMPTION	1500 LT./MIN. (396 US gal/MIN.)	
TANK	100 LT. (26 US gal)	
STANDARD VOLTAGE	ANY 60HZ 3PH	
WEIGHT WITHOUT OIL/WATER	2150 Lbs	

INCLUDED ACCESSORIES

- SUCTION FILTER
- DELIVERY FILTER
- INTERNAL OIL PROTECTING MESH
- SHELVES FOR TOOLS
- PRESSURE PEAK MEMORY
- LEVEL WARNING SIGNAL
- AIR-OIL PRESSURE MULTIPLIER

OPTIONAL

SAE CONNECTIONS



ADAPTORS



BURST-PROOF PROTECTION



3000 mm TESTING CHAMBER



WASHING DEVICE



PC CONNECTION



INDUSTRY 4.0

