



TUBOMATIC H83 ES

CODE: TUBH83ES

CRIMPING (STANDARD VOLUME CRIMPING)

TUBOMATIC H83 EL

CODE: TUBH83EL

CRIMPING (STANDARD VOLUME CRIMPING)



ALSO AVAILABLE WITH
PORTABLE DIES HOLDER

MAIN FEATURES



IDEAL FOR ANY TYPE OF
FITTING



MACH TOUCH-SCREEN
ELECTRONIC CONTROL
H83 ES



ELECTRO-MECHANICAL
CONTROL
H83 EL



WARNING LED
H83 EL



VERNIER DIAL
H83 EL



IDEAL FOR YOUR WORKSHOP



PROTRACTOR FOR FITTINGS
ORIENTATION

TECHNICAL DATA

	H83 ES	H83 EL
CRIMPING FORCE	198 TON	198 TON
6 SPIRALS 2 PIECES	1"	1"
4 SH 2 PIECES	1" 1/2 [◇]	1" 1/2 [◇]
4 SH 2 PIECES	1" 1/4	1" 1/4
MAX Ø	62 mm (2.4") [◇]	62 mm (2.4") [◇]
CRIMPING/HOUR	1083 [□]	1083 [□]
DIE OPENING	D. + 1.6"	D. + 1.6"
90° FITTINGS	1"1/4	1"1/4
STANDARD VOLTAGE	ANY 60HZ 3PH	ANY 60HZ 3PH
MOTOR POWER	4 KW (5 HP)	4 KW (5 HP)
DIMENSIONS LXXHXH	27.2"X24.3"X29.9"	27.2"X25.6"X26.2"
WEIGHT WITHOUT OIL	485 Lbs	485 Lbs
OIL (NOT INCLUDED)	18.5 US gal	18.5 US gal
SETTABLE RE-OPENING TIME AFTER CRIMPING	-	■
SETTABLE CRIMPING TIME	-	■
USB KIT	■	-

ACCESSORIES

		H83 ES	H83 EL
PRESSURE CONTROL SYSTEM KIT		■	-
QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL		■	-
MULTISTEP CRIMPING DIAMETERS		■	-
DISPENSER + PATENTED QUICK CHANGE TOOL		■	■
ELECTRIC PEDAL		INCLUDED	INCLUDED
BASE		■	■
BACK MIRROR		■	■

DIAMETER (mm)	10	12	14	16	19	22	25	29	34	38	42	46	50
	DIES LENGTH (mm)												
H83 ES	60	60	60	60	60	60	60	70	70	85	85	85	85
H83 EL													

◇ THEORETICAL WITH 1/2" Δ Ø 6 mm HOSE
◇ WITH SPECIAL DIES Ø 54 mm UPON REQUEST
ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED

Product specifications could be modified without prior notice.