

TUBOCUT 5

CODE: TUBOCUT5
CUTTING



AUTOMATIC EQUIPMENT IDEAL
FOR VOLUME PRODUCTION

MAIN FEATURES



TOUCH-SCREEN
ELECTRONIC CONTROL



RECESSED BLADE
FOR A GREATER SAFETY



HOSE MARKING SYSTEM



SUCTION CONNECTION



DRAWER FOR INTERNAL
CLEANING



IDEAL FOR VOLUME
PRODUCTION

TECHNICAL DATA

HOSE OD	0.3"-1.6"
CUTTING TOLERANCE	± 0,5%
MIN. CUTTING LENGTH	9.8"
MAX. CUTTING LENGTH	3936.9"
BELT SPEED	15 - 30 - 40 MT/MIN.
BLADE Ø	520 mm (20.4")
REVOLUTIONS/MINUTE	2800
MAX. REEL WEIGHT	330 Lbs
STANDARD VOLTAGE	ANY 60HZ 3PH
BLADE MOTOR POWER	5.5 KW (7.5 HP) - A= 9.85
TRANSMISSION BELT MOTOR POWER	0.35 KW (0.5 HP)
SUCTION HOSE CONNECTION Ø	3.9"
PNEUMATIC INPUT	MAX 6 BAR (84 PSI)
CUTTING MACHINE WEIGHT	1653 Lbs
HOSE FEEDING SYSTEM WEIGHT	552 Lbs
CONVEYOR BELT WEIGHT	240 Lbs
CUTTING MACHINE DIMENSIONS LXWXH	57"x33.4"x57"
WINDER DIMENSIONS LXWXH	163.3"x41.3"x49.2"
CONVEYOR BELT DIMENSIONS LXWXH	84.6"x19.6"x39.3"

ACCESSORIES

FUME EXTRACTOR



CONVEYOR BELT



READING AND IDENTIFICATION BARCODE SYSTEM



HOSE MARKING SYSTEM WITH USER INTERFACE



LAN AND USB CONNECTION CONFIGURATION (INCLUDED)



OPTIONAL

INDUSTRY 4.0

4.0



HOSE WINDING SYSTEM



MOTORIZED HOSE DRIVING
SYSTEM



LOOP CONTROL DEVICE



CUTTING MACHINE WITH
TOUCH-SCREEN PLC



CONVEYOR BELT



PRINTER