

C42
CODE: CURVC42
BENDING

CMS42
CODE: CURCMS42
BENDING

M18
CODE: CURVM18
BENDING



MOUNTED ON TOOL-HOLDER CABINET



SUITABLE TO BE FIXED TO ANY VICE
ADATTA A ESSERE FISSATA SU QUALSIASI
MORSA DA BANCO

MAIN FEATURES



IDEAL FOR VOLUME
PRODUCTION
C42



ELECTRIC LIMIT SWITCH
C42



DOUBLE EFFECT MANUAL
PUMP
CMS42



EQUIPPED WITH WHEELS
C42



MANUALLY OPERATED
CMS42 - M18

TECHNICAL DATA

| | C42 | CMS42 | M18 |
|--------------------|----------------------------------|-----------------------|-----------------------|
| BENDING | 1/4" → 1" 1/2 X 0.15" | 1/4" → 1" 1/2 X 0.15" | 1/4" → 5/8" |
| MATERIALS | AISI 316 TI - ST 37.4 | AISI 316 TI - ST 37.4 | AISI 316 TI - ST 37.4 |
| DIMENSIONS LXWXH | 26.7"x34.6"x35.8" | 16.5"x30.7"x38.5" | 28.3"x5.1"x4.9" |
| WEIGHT WITHOUT OIL | 225 Lbs | 90 Lbs | 22 Lbs |
| OIL | 5 LT. (1 US gal) NOT INCLUDED | INCLUDED | - |
| STANDARD VOLTAGE | ANY 60HZ 3PH/1PH | - | - |
| MOTOR POWER | 1.1 KW (1.5 HP) | - | - |

INCLUDED ACCESSORIES

| | C42 | CMS42 | M18 |
|-------------------------------|-----|-------|-----|
| MECHANICAL LIMIT SWITCH | - | ■ | - |
| BENDING TOOLS AND TOOL HOLDER | - | - | ■ |
| VICE FIXING PIN | - | - | ■ |

EQUIPMENT SUITABLE TO PROCESS RIGID TUBES
IN STAINLESS (AISI 316 TI) AND CARBON (ST 37.4) STEEL

MAX THICKNESS

| C42 | | | | | | | | |
|-----------------------|------|------|----|----|----|------|------|----|
| 4 mm | Ø 38 | | | | | | | |
| 3 mm | Ø 42 | | | | | | | |
| M18 | | | | | | | | |
| Ø | 6 | 8 | 10 | 12 | 14 | 15 | 16 | 18 |
| MEDIUM BENDING RADIUS | 33,5 | 33,5 | 36 | 36 | 36 | 43,5 | 43,5 | 51 |