

SPF6
CODE: SPELSPF6
SKIVING

SPF3
CODE: SPELSPF3
SKIVING

SPF2/MS
CODE: SPELSPF2MS
SKIVING



SELF-CENTERING
PNEUMATIC VICE

MAIN FEATURES



SIMULTANEOUS SKIVING

SPF6
SPF3



INTERNAL SKIVING



EXTERNAL SKIVING



DRAWER FOR SHAVINGS



IDEAL FOR VOLUME
PRODUCTION

SPF6



PNEUMATIC VICE

SPF6
SPF3
SPF2/MS OPTIONAL



SAFETY DEVICE WHICH PREVENTS
FROM OPERATING THE MACHINE WHEN
THE CASING IS OPEN

SPF6



PREASSEMBLY

SPF6



SAFETY PROTECTIONS

TECHNICAL DATA

	SPF6	SPF3	SPF2/MS
EXTERNAL SKIVING	3"	2"	2"
INTERNAL SKIVING	3"	2"	2"
INSERT CAPACITY	3"	-	-
SIMULTANEOUS INT-EXT SKIVING	2"	2"	-
REVOLUTIONS/MINUTE	300	200	300
PNEUMATIC INPUT	MAX 8 BAR (115 PSI)	MAX 7 BAR (100 PSI)	MAX 7 BAR (100 PSI) OPTIONAL
WORKING CYCLE	SEMI-AUTOMATIC	MANUAL	-
WEIGHT	727 Lbs	319 Lbs	172 Lbs
DIMENSIONS LXWXH	41.3"x51.1"x43.3"	28.5"x31.8"x42.1"	26.9"x19.6"x44"
STANDARD VOLTAGE	ANY 60HZ 3PH	ANY 60HZ 3PH/1PH	ANY 60HZ 3PH/1PH
MOTOR POWER	1.1 KW (1,5 HP)	0.75 KW (1 HP)	0.75 KW (1 HP)

ACCESSORIES

	SPF6	SPF3	SPF2/MS
ELECTRIC PEDAL (INCLUDED)		■	■
TOOL HOLDER			
	INCLUDED		
TOOL HOLDER STAND		-	■

SPF6



SKIVING MANDREL

SPF6



SELF-CENTERING
PNEUMATIC VICE

SPF6



INSERT MANDREL

SPF3



SKIVING MANDREL

SPF2/MS



SKIVING MANDREL

SPF2/MS



OPTIONAL
PNEUMO-HYDRAULIC VICE