

# H47<sup>e</sup>PUMP

BATTERY OPERATED CRIMPER

**CODE: TUBH47E + H47EELPUMP**  
CRIMPING (SERVICE)



COMPACT AND PORTABLE  
EQUIPMENT, IDEAL  
FOR ON-SITE SERVICE

# TF1<sup>e</sup>CUT

BATTERY OPERATED CUTTER

**CODE: TAGLTF1D/ECO**  
CUTTING (SERVICE)



COMPACT AND PORTABLE  
EQUIPMENT, IDEAL  
FOR ON-SITE SERVICE

## MAIN FEATURES



LED INDICATING WHEN  
THE SET CRIMPING  
DIAMETER IS REACHED  
**H47 EPUMP**



SAFETY PROTECTIONS  
**TF1 ECUT**



SUCTION CONNECTION  
**TF1 ECUT**



MANUALLY OPERATED  
**TF1 ECUT**



RECESSED BLADE  
FOR A GREATER SAFETY  
**TF1 ECUT**



IDEAL FOR  
ON-SITE SERVICE





BATTERY

## TECHNICAL DATA

	H47 ePUMP
CRIMPING FORCE	110 US TON
CAPACITY	1" 2 SP
MAX Ø	46 mm (1.8") *
DIE OPENING	Ø + 0.7"
90° FITTINGS	3/8"
DIMENSIONS LXWXH	7.9"x12.4"x12.6"
PUMP DIMENSION WITH BATTERY LXWXH	11.4"x4.7"x8.7"
BATTERY	14,4 V - 4 AH
H47 WEIGHT	52 Lbs
PUMP WEIGHT	18 Lbs OIL EXCLUDED / 20 Lbs OIL INCLUDED
OIL	1 LT (0.26 US gal)
PRESSURE	FROM 0.18 TO 0.02 US gal/MIN
CYLINDER	SINGLE EFFECT

## ACCESSORIES

	H47 ePUMP
TOOL FOR DIE CHANGE	
DIE HOLDER CASE + N.8 DIES + DIE CHANGING TOOL	

## TECHNICAL DATA

	TF1 eCUT
6 SPIRALS	1"
4 SPIRALS	1" 1/4
2 BRAIDS	1" 1/4
MAX Ø	2.2"
REVOLUTIONS/MINUTE	5000
BLADE Ø	DIAMOND BLADE 6.5"x0.05"x0.8"
BATTERY	18 V - 5 AH
DIMENSIONS LXWXH	12.8"x13.8"x15.8"
WEIGHT	15 Lbs

DIAMETER (mm)	10	12	14	16	19	22	25	29
DIES LENGTH (mm)	55	55	55	55	55	55	65	65
H47 EPUMP	55	55	55	55	55	55	65	65

\*DIE HOLDER \*  
ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED.