

**TF6**  
CODE: TAGLTF6D  
CUTTING

**TF5**  
CODE: TAGLTF5D  
CUTTING

**TF4**  
CODE: TAGLTF4D  
CUTTING



MAIN FEATURES



SELF-BRAKING MOTOR



TOOTHED BLADE



SELF-CENTERING  
HOSE SUPPORT



DRAWER FOR INTERNAL CLEANING



RECESSED BLADE  
FOR A GREATER SAFETY



SAFETY PROTECTIONS



TOUCH-SCREEN  
ELECTRONIC CONTROL  
**TF6**



DIGITAL STROKE  
COUNTER  
**TF5  
TF4**

TECHNICAL DATA

	TF6	TF5	TF4
6 SPIRALS	3"	2" 1/2	2"
4 SPIRALS	3"	3"	2" 1/2
2 BRAIDS	3"	3"	3"
INDUSTRIAL HOSE	4"	4"	3"
MAX Ø	6.2"	6.2"	3.9"
REVOLUTIONS/ MINUTE	2900	2900	2900
PNEUMATIC INPUT	-	MAX 7 BAR (100 PSI)	MAX 7 BAR (100 PSI)
BLADE Ø	650 mm (25.6")	520 mm (20.4")	400 mm (15.7")
STANDARD VOLTAGE	ANY 60HZ 3PH	ANY 60HZ 3PH	ANY 60HZ 3PH
DIMENSIONS LXWXH	49.2"x34.2"x63.5"	48"x26.1"x62.5"	44"x23.8"x57.2"
WEIGHT	1027 Lbs	854 Lbs	717 Lbs
SELF BRAKING MOTOR POWER	11 KW (15 HP) - A= 23	7.5 KW (10 HP) - A= 13.80	5.5 KW (7.5 HP) - A= 9.85

ACCESSORIES

	TF6	TF5	TF4
MEASURING HOSE HOLDER		■	■
CENTERING DEVICE + METER COUNTER (MAX 2")		■	■
FUME EXTRACTOR		■	■
BLOWING KIT		■	■
PEDAL-EQUIPPED ELECTRIC CONTROL (INCLUDED)		■	-
PEDAL-EQUIPPED PNEUMATIC CONTROL (INCLUDED)		-	■
CUTTING SPEED ADJUSTMENT DEVICE (INCLUDED)	-	■	■

TF6 ALSO AVAILABLE WITHOUT SELF-BRAKING MOTOR  
CODE: TAGLTF6D/NB