

UNISPEED USFL/01 MAN

CODE: USFLMAN
FLARING & PREASSEMBLY



UNISPEED USFL 015 MAN

CODE: USFL015MAN
PREASSEMBLY



SUITABLE TO BE FIXED TO ANY VICE AND FOR LL, L, S
SERIES TOOLS AND FOR TUBES WITH EXTERNAL Ø 6-15 mm.

MAIN FEATURES



DIN2353 RINGS
PREASSEMBLY



37° FLARING WITH THE ADDITION OF
A DEDICATED STEEL FLARING BLOCK
USFL/01 MAN



IDEAL FOR ON-SITE
SERVICE



MANUALLY OPERATED

TECHNICAL DATA

	USFL/01 MAN	USFL 015 MAN
24° PREASSEMBLY	6→42X4 mm	6S - 15L
37° FLARING	1/4 →1" 1/2 X 0.15"	-
MATERIALS	AISI 316 TI - ST 37.4	AISI 316 TI - ST 37.4
WEIGHT	84 Lbs	26 Lbs
DIMENSIONS LXWXH	13.7"X15.7"X10.6"	11.2"X4.1"X4.1"
LEVEL LENGTH	-	31.4"

USFL/01 MAN: 37° FLARING TOOLS:
supplied according to UNI ISO 8434-2 and DIN 3949 regulations

MANUAL PREASSEMBLING TOOL

Manual preassembling tool (6→42)



OPTIONAL

	USFL/01 MAN	USFL/015 MAN
37° FLARING BLOCK (6→42)		-
TOOL HOLDER (6→42)		-

EQUIPMENT SUITABLE TO PROCESS RIGID TUBES
IN STAINLESS (AISI 316 TI) AND CARBON (ST 37.4) STEEL

TEMPLATE FOR PREASSEMBLING TOOL CONTROL

Template for preassembling tool control (6→42)

