

BC 1200/E ES

CODE: BC1200EES
TESTING

BC 1200/E

CODE: BC1200E
TESTING



PROVIDED WITH ONE Ø 1/4" QUICK
COUPLING AND HYDRAULIC MULTIPLIER

MAIN FEATURES



TOUCH-SCREEN
ELECTRONIC CONTROL
BC 1200/E ES



NOT SUITABLE
FOR BURST TEST



INTERNAL LIGHTING
BC 1200/E ES



SHOCK-PROOF
TESTING WINDOWS
BC 1200/E ES



SLIDING MANIFOLD
BC 1200/E ES



USB CONNECTION
CONFIGURATION
BC 1200/E ES



PDF FILES PRINTING
BC 1200/E ES



MANUALLY OPERATED
BC 1200/E

TECHNICAL DATA

	BC1200/E ES	BC1200/E
STATIC PRESSURE	1200 BAR (17400 PSI)	1200 BAR (17400 PSI)
DYNAMIC PRESSURE	1200 BAR (17400 PSI)	1200 BAR (17400 PSI)
MIN. STARTING PRESSURE	100 BAR (1450 PSI)	100 BAR (1450 PSI)
PRESSURE CONTROL	AUTOMATIC	MANUAL
TEST	AUTOMATIC	MANUAL
TYPE OF DRIVE	HYDRAULIC INTENSIFIER	HYDRAULIC INTENSIFIER
TESTING LIQUID	FLUID	FLUID
N° MANIFOLDS	2	2
N° CONNECTIONS PER MANIFOLD	N°06 SPECIAL QUICK CONNECTION N°2 1/4" BSP	N°01 SPECIAL QUICK CONNECTION N°2 1/4" BSP
LIQUID FILLING	AUTOMATIC	MANUAL
FILLING FLOW	17 LT./MIN. (4.5 US gal/MIN.)	17 LT./MIN. (4.5 US gal/MIN.)
PRESSURE DISCHARGE	AUTOMATIC	MANUAL
PRESSURE GAUGE	-	ANALOGIC
DOOR MECHANICAL SAFETY DEVICE	AUTOMATIC	AUTOMATIC
DOOR ELECTRIC SAFETY DEVICE	AUTOMATIC	AUTOMATIC
STANDARD CHAMBER DIMENSIONS	78.7"X32.6"	78.7"X32.6"
BENCH DIMENSIONS	98.4"X37.5"X47.2"	98.4"X34.4"X47.2"
TANK	110 LT. (29 US gal)	110 LT. (29 US gal)
STANDARD VOLTAGE	ANY 60HZ 3PH	ANY 60HZ 3PH
WEIGHT WITHOUT OIL	1323 Lbs	1014 Lbs
FIXED VOLUME MULTIPLIER	OIL VOLUME 0.32 LT. (0.08 US gal)	OIL VOLUME 0.32 LT. (0.08 US gal)

INCLUDED ACCESSORIES

SUCTION FILTER

DELIVERY FILTER

INTERNAL OIL PROTECTING MESH (BC 1200/E ES)

SHELVES FOR TOOLS (BC 1200/E ES)

MANUAL DOOR OPENING (BC 1200/E ES)

OPTIONAL

	BC1200/E ES	BC1200/E
PC CONNECTION	■	-
ADAPTORS: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2"	■	■
PRESSURE REPORT KIT	-	■



ADAPTORS



ADAPTORS WITH QUICK COUPLING
BC 1200/E ES



ADAPTORS WITH QUICK COUPLING
BC 1200/E