

TUBOMATIC H135 ES

CODE: TUBH135ES

CRIMPING (STANDARD VOLUME CRIMPING)

TUBOMATIC H135 EL

CODE: TUBH135EL

CRIMPING (STANDARD VOLUME CRIMPING)

TUBOMATIC H135/E EL

CODE: TUBH135/E EL

CRIMPING (STANDARD VOLUME CRIMPING)



ALSO AVAILABLE WITH
PORTABLE DIES HOLDER



MAIN FEATURES



IDEAL FOR ANY TYPE OF FITTING



MACH TOUCH-SCREEN
ELECTRONIC CONTROL

H135 ES



ELECTRO-MECHANICAL
CONTROL

**H135 EL
H135/E EL**



WARNING LED

H135 EL



VERNIER DIAL

**H135 EL
H135/E EL**



IDEAL FOR YOUR WORKSHOP



PROTRACTOR FOR FITTINGS
ORIENTATION

**H135 ES
H135 EL**

TECHNICAL DATA

	H135 ES	H135 EL	H135/E EL
CRIMPING FORCE	345 US TONS	345 US TONS	330 US TONS
6 SPIRALS 2 PIECES	2"	2"	2"
INDUSTRIAL HOSE	3"	3"	3"
MAX Ø	135 mm (5.3") ◇	120 mm (4.7") ◇	111 mm (4.3") ◇
CRIMPING / HOUR	865 □	865 □	271 □
DIE OPENING	Ø + 1.6"	Ø + 1.6"	Ø + 1.6"
90° FITTINGS	2"	2"	2"
STANDARD VOLTAGE	ANY 60HZ 3PH	ANY 60HZ 3PH	230V 60HZ 1PH
MOTOR POWER	5.5 KW (7.5 HP) - A= 10.64	5.5 KW (7.5 HP) - A= 10.64	5.5 KW (7.5HP)
DIMENSIONS LXWXH	32.2"X29.5"X32.2"	32.2"X25.9"X32.2"	30.7"X24.8"X28"
WEIGHT WITHOUT OIL	1047 Lbs	1036 Lbs	704 Lbs
OIL (NOT INCLUDED)	110 LT. (29 US gal)	110 LT. (29 US gal)	55 LT. (14 US gal)
SETTABLE RE-OPENING TIME AFTER CRIMPING	-	■	-
SETTABLE CRIMPING TIME	-	■	-
USB KIT	■	-	-

ACCESSORIES

	H135 ES	H135 EL	H135/E EL
PRESSURE CONTROL SYSTEM	■	-	-
QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL	■	-	-
MULTISTEP CRIMPING DIAMETERS	■	-	-
PATENTED QUICK CHANGE TOOL	■	■	■
BASE	■	■	■
BACK MIRROR	■	■	-
CLEANING AND MAINTENANCE KIT	■	■	■
ELECTRIC PEDAL	INCLUDED		

DIAMETER (mm)	10	12	14	16	19	22	25	29	34	38	42	46	50	54	58	63	69	73
	DIES LENGTH (mm)																	
H135 ES - H135 EL H135/E EL	60	60	60	60	60	60	60	70	70	85	85	95	95	95	95	100	100	100

◇ WITH SPECIAL DIES Ø 104 mm UPON REQUEST
△ THEORETICAL WITH 1/2" Δ Ø 6 mm HOSE
ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED

Product specifications could be modified without prior notice.