

TUBOMATIC H170 ES

CODE: TUBH170ES

CRIMPING (STANDARD VOLUME CRIMPING)

TUBOMATIC H170 EL

CODE: TUBH170EL

CRIMPING (STANDARD VOLUME CRIMPING)



WIDE OPENING.
IDEAL FOR BIG FLANGES



MAIN FEATURES



IDEAL FOR ANY TYPE OF FITTING



MACH TOUCH-SCREEN
ELECTRONIC CONTROL
H170 ES



INDUSTRIAL HOSE CRIMP
CALCULATOR
H170 ES



WARNING LED
H170 EL



VERNIER DIAL
H170 EL



ELECTRO-MECHANICAL
CONTROL
H170 EL



IDEAL FOR YOUR WORKSHOP



PROTRACTOR FOR FITTINGS
ORIENTATION

TECHNICAL DATA

	H170 ES	H170 EL
CRIMPING FORCE	308 US TONS	308 US TONS
6 SPIRALS 2 PIECES	1" 1/2	1" 1/2
4 SH 2 PIECES	2"	2"
INDUSTRIAL HOSE	4"	4"
MAX Ø	170 mm (6.7")	170 mm (6.7")
CRIMPING / HOUR	865 ◇	865 ◇
DIE OPENING	Ø + 2.4"	Ø + 2.4"
90° FITTINGS	2"	2"
STANDARD VOLTAGE	ANY 60HZ 3PH	ANY 60HZ 3PH
MOTOR POWER	5.5 KW (7 HP) - A 10.74	5.5 KW (7 HP) - A 10.74
DIMENSIONS LXWXH	32.2"x31.9"x32.9"	32.2"x25.9"x32.9"
WEIGHT WITHOUT OIL	1102 Lbs	1102 Lbs
OIL (NOT INCLUDED)	110 LT. (29 US gal)	110 LT. (29 US gal)
SETTABLE RE-OPENING TIME AFTER CRIMPING	-	■
SETTABLE CRIMPING TIME	-	■
USB KIT	■	-

ACCESSORIES

		H170 ES	H170 EL
PRESSURE CONTROL SYSTEM KIT		■	-
QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL		■	-
MULTISTEP CRIMPING DIAMETERS		■	-
DISPENSER + PATENTED QUICK CHANGE TOOL		■	■
BASE		■	■
BACK MIRROR		■	■
CLEANING AND MAINTENANCE KIT		■	■
ELECTRIC PEDAL		INCLUDED	

DIAMETER (mm)	10	12	14	16	19	22	25	29	34	38	42	46	50	54	58	63	69	73	77	86	90	96	103	106	111	116	121	126	131	
	DIES LENGTH (mm)																													
H170 ES H 170 FL	60	60	60	60	60	60	60	70	70	85	85	95	95	95	95	100	100	100	120	120	150	120	130	130	130	130	130	130	130	130

◇ THEORETICAL WITH 1/2" Δ Ø 6 mm HOSE
ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED

Product specifications could be modified without prior notice.