

# TUBOMATIC V59 ES

CODE: TUBV59ES

CRIMPING (HIGH VOLUME CRIMPING)



## MAIN FEATURES



ES4 TOUCH-SCREEN  
ELECTRONIC CONTROL



SELF-LUBRICATING  
MOVING PARTS



SILENT PUMP



6 O'CLOCK DIE  
IN FIXED POSITION FOR  
A BETTER STABILITY  
OF THE HOSE



NARROW CRIMPING HEAD  
FOR BIG FLANGES  
AND 90° FITTINGS



PROTRACTOR  
FOR FITTINGS  
ORIENTATION



SERVICE COUNTER



IDEAL FOR  
VOLUME  
PRODUCTION

## TECHNICAL DATA

CRIMPING FORCE	155 US TONS
6 SPIRALS 2 PIECES	1"
4 SPIRALS 2 PIECES	1" 1/4
2 BRAIDS 2 PIECES	1" 1/2 *
MAX Ø	67 mm (2.6") ◇
CRIMPING / HOUR	3900 □
CLOSING SPEED	0.4"/SEC
CRIMPING SPEED	0.2"/SEC
OPENING SPEED	0.4"/SEC
DIE OPENING	Ø + 1.9"
OPENING WITHOUT DIES	4.6"
STANDARD VOLTAGE	ANY 60HZ 3PH
MOTOR POWER	5,5 KW (7.5 HP) - A= 10.64
DIMENSIONS LXWXH	25.9"X28.3"X58.6"
WEIGHT WITHOUT OIL	1199 Lbs
OIL (NOT INCLUDED)	70 LT. (18 US gal)

## ACCESSORIES

CRIMPING THROUGH PRESSURE CONTROL (INCLUDED)	
INDUSTRY 4.0 KIT	<b>4.0</b>
CRIMPING DIAMETER SELF CORRECTION	
DATA SAVE ON CSV FILE	
CRIMPING SPEED CONTROL SYSTEM	
QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL (INCLUDED)	
MULTISTEP CRIMPING DIAMETERS	
BARCODE	
CAMERA	
LAN CONNECTION TO PC	
ELECTRIC PEDAL INCLUDED	
FRONT AND REAR PROTECTION NET WITH ACTIVATION LIMIT SWITCH	
DISPENSER + PATENTED QUICK CHANGE	
BACK MIRROR	

DIAMETER (mm)	10	12	14	16	19	22	25	29	34	38	42	46
DIES LENGTH (mm)	60	60	60	60	60	60	60	75	75	75	75	75
V59 ES	60	60	60	60	60	60	60	75	75	75	75	75

□ THEORETICAL WITH 1/2" Δ Ø 6 mm HOSE

◇ WITH SPECIAL DIES Ø 54 mm UPON REQUEST

\* CON WHIT SPECIAL DIES

ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED