

BC 4500 ES

CODE: BC4500ES

TESTING



PNEUMO-HYDRAULIC PUMP

MAIN FEATURES



BURST TESTS



TOUCH-SCREEN
ELECTRONIC CONTROL



INTERNAL LIGHTING



SHOCK-PROOF
TESTING WINDOWS



BURST-PROOF
PROTECTIONS



SLIDING MANIFOLD



TEMPERATURE
WARNING SIGNAL



AUTOMATIC
DOOR OPENING



USB CONNECTION
CONFIGURATION



PDF FILES PRINTING

TECHNICAL DATA

STATIC PRESSURE	4500 BAR (65250 PSI)
DYNAMIC PRESSURE	4500 BAR (65250 PSI)
MIN. STARTING PRESSURE	100 BAR (1450 PSI)
PRESSURE CONTROL	AUTOMATIC
TEST	AUTOMATIC
TYPE OF DRIVE	PNEUMATIC INTENSIFIER
TESTING LIQUID	FLUID
N° MANIFOLDS	2
N° CONNECTIONS PER MANIFOLD	2 X M16 X 1.5 mm
LIQUID FILLING	SEMI-AUTOMATIC
FILLING FLOW	25 LT./MIN. (6.5 US gal/MIN.)
PRESSURE PUMP FLOW	0.32 LT/MIN (0.08 US gal/MIN.)
PRESSURE DISCHARGE	AUTOMATIC
DOOR ELECTRIC SAFETY DEVICE	AUTOMATIC
PRESSURE GAUGE	DIGITAL
STANDARD CHAMBER DIMENSIONS	86.6"X35.4"
BENCH DIMENSIONS	97.2"X37.4"X51.1"
AIR CONSUMPTION	1500 LT./MIN. (396 US gal/MIN.)
TANK	100 LT. (26 US gal)
STANDARD VOLTAGE	ANY 60HZ 3PH
WEIGHT WITHOUT OIL	1500 Lbs

INCLUDED ACCESSORIES

SUCTION FILTER

DELIVERY FILTER

SHELVES FOR TOOLS

PRESSURE PEAK MEMORY

LEVEL WARNING SIGNAL

OPTIONAL

3000 mm TESTING CHAMBER



ADAPTORS



PC CONNECTION



INDUSTRY 4.0

4.0