

BC 1200 ECO AND BC 1200 ECO WATER

CODE: BC1200ECO - BC1200ECO/WATER

TESTING



WATER VERSION WITH CHAMBER AND COMPONENTS IN STAINLESS STEEL

PROVIDED WITH ONE Ø 1/4" GAS QUICK COUPLING AND PNEUMO-HYDRAULIC PUMP

MAIN FEATURES



MANUALLY OPERATED



NOT SUITABLE FOR BURST TEST



SHOCK-PROOF TESTING WINDOWS



WATER TESTS

BC 1200ECO/WATER

TECHNICAL DATA

STATIC PRESSURE	1200 BAR (17400 PSI)
MIN. STARTING PRESSURE	70 BAR (1015 PSI)
PRESSURE CONTROL	MANUAL
TEST	MANUAL
TYPE OF DRIVE	PNEUMATIC INTENSIFIER
TESTING LIQUID	FLUID OR WATER
N° MANIFOLDS	1
N° CONNECTIONS PER MANIFOLD	N. 1 SPECIAL QUICK CONNECTION
LIQUID FILLING	MANUAL
PRESSURE PUMP FLOW	0.3 LT./MIN. (0.08 US gal/MIN)
PRESSURE DISCHARGE	MANUAL
STANDARD CHAMBER DIMENSIONS	47.2"X21.6"X9.8"
BENCH DIMENSIONS	59"X23.6"X47.2"
TANK	30 LT. (8 US gal)
WEIGHT WITHOUT OIL (BC 1200 ECO)	364 Lbs
WEIGHT WITHOUT WATER (BC 1200 ECO WATER)	286 Lbs
PRESSURE GAUGE	ANALOGIC

INCLUDED ACCESSORIES

SUCTION FILTER

DELIVERY FILTER

INTERNAL OIL PROTECTING MESH

ADAPTOR WITH QUICK COUPLING 1/4"

OPTIONAL

ADAPTOR: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2"

PRESSURE REPORT KIT



ADAPTORS



ADAPTOR WITH QUICK COUPLING