

CENTER MAXI

CODE: CENTERMAXI
MULTIFUNCTIONAL UNITS

CENTER JUNIOR

CODE: CENJUUSFL
MULTIFUNCTIONAL UNITS

MINI CENTER

CODE: CENECO
MULTIFUNCTIONAL UNITS



DOUBLE WORKING LEVEL: UPPER LEVEL FOR BENDS UP TO 180°, LOWER LEVEL FOR STANDARD TUBES

MAIN FEATURES



BENDING



37° FLARING



DEBURRING



DIN2353 RINGS
PREASSEMBLING



CUTTING

CENTER MAXI
CENTER JUNIOR



ELECTRONIC CONTROL

CENTER MAXI



IDEAL FOR VOLUME
PRODUCTION

CENTER MAXI



EQUIPPED WITH
WHEELS



EQUIPPED WITH COMPRES-
SOR FOR THE INTERNAL
CLEANING

CENTER JUNIOR



SAFETY PROTECTIONS

TECHNICAL DATA

	CENTER MAXI	CENTER JUNIOR	MINI CENTER
24° PREASSEMBLY	6→18 ON UPPER LEVEL	6→42X4 mm	6→42X4 mm
37° FLARING	1/4"→1 1/2 X 0.15" ON UPPER LEVEL	1/4"→1 1/2 X 0.15"	1/4"→1 1/2 X 0.15"
BENDING Ø (GENERAL TUBE)	*1/4"→1 1/2	*1/4"→1 1/2 X 0.15"	1/4"→1 1/2 X 0.15"
BENDING Ø (AISI 316 TI)	1" 1/4 X 0.15" 1" 1/2 X 0.12"	-	-
BENDING Ø (ST 37.4)	1" 1/4 X 0.20" 1" 1/2 X 0.12"	-	-
MAX BENDING ANGLE	180°	-	-
90° BENDING TIME	6 SEC.	-	-
CUTTING	MAX Ø 4.9"	MAX Ø 3.9"	-
INT/EXT DEBURRING	6 - 42 mm (1/4"→1 1/2)	6 - 42 mm (1/4"→1 1/2)	6 - 42 mm (1/4"→1 1/2)
MATERIALS	AISI 316 TI - ST 37.4	AISI 316 TI - ST 37.4	AISI 316 TI - ST 37.4
ELECTRONIC CONTROL	TOUCH SCREEN	-	-
DIMENSIONS LxWxH	55.1"x31.4"x59"	59.6"x39.3"x47.6"	28.3"x36.2"x50.9"
WEIGHT WITHOUT OIL	882 Lbs	672 Lbs	454 Lbs
STANDARD VOLTAGE	ANY 60HZ 3PH	ANY 60HZ 1PH	ANY 60HZ 1PH
MOTOR POWER	MAX 4.5 KW (6 HP)	MAX 4.6 KW (6.2 HP)	MAX 1.7 KW (2.3 HP)
COMPRESSED AIR	-	220 LT./MIN. (58 US gal/MIN.)	-
OIL	15 LT. (4 US gal) NOT INCLUDED	5 LT. (1 US gal) NOT INCLUDED	3 LT. (0.8 US gal) INCLUDED

OPTIONAL

	C. M.	C. J.	M. C.
PEDAL FOR C50 ES		■	-
PEDAL FOR USFL 24/37 ES		■	-
TOOL HOLDER		INCLUDED ■	■
TUBE DRIVING SYSTEM		■	-

EQUIPMENT SUITABLE TO PROCESS RIGID TUBES
IN STAINLESS (AISI 316 TI) AND CARBON (ST 37.4) STEEL

*With special tool Ø 5 mm upon request
Special equipment with different bending radius are available upon request